

OUT61317

1967 MAR 2 22 07Z

P 022139Z MAR 67
FM NPIC WASHDC
TO RUCSAAA/SAC OFFUTT AFB OMAHA NEB
RUCVAAA/4080 STRAT WG OL 19 BARKSDALE AFB LA
RUCVAAA/2D RTS BARKSDALE AFB LA
RUEPJS/DIA WASHDC
RUCIJRA/NAVRECONTECHSUPPCEN SUITLAND MD
RUEPIA/CIA WASHDC
RUWBKNA/15TH AF MARCH AFB RIVERSIDE CALIF
RUCVAAA/2 AF BARKSDALE AFB LA

BT
SECRET CITE NPIC 9981.

15TH AF (FOR DI), SAC (FOR DIM/GLASS LAMP/DOCR, DM 4)

2D AF (FOR DI).

1. CAMERA B-15 WAS USED IN MISSION G 948 FLOWN ON 28 FEBRUARY 1967. PROCESSING WAS ACCOMPLISHED BY NAV RECON TECH SUPPCEN.

2. ORIGINAL NEGATIVE:

A. DENSITY AND RESOLUTION ARE GOOD.

B. 9R SIDE: EDGE STATIC ON BOTH THE INBOARD AND OUTBOARD EDGES, ROLLER CHATTER ON THE INBOARD EDGE, AND AN OBSTRUCTION IN THE POSITION INDICATOR AREA APPEAR THROUGHOUT THE MISSION. A PLUS DENSITY STREAK 1/2 INCH WIDE AND 3 TO 6 INCHES LONG, AND A DIAGONAL STREAK 1/2 INCH BY 3 INCHES AND LOCATED ABOUT 3 INCHES FROM THE FIRST STREAK APPEAR AT THE OUTBOARD EDGE IN VARYING DENSITY IN FRAMES 013, 140, 352, 522, 613, 763, AND 1037. FRAME 1127 CONTAINS A HEAT SPLICE. FRAME 1832 CONTAINS A MANUFACTURING SPLICE. LAST FRAME IS 2335.

C. 9L SIDE: SLIGHT INBOARD EDGE STATIC AND A PLUS DENSITY AREA NEAR THE VERTICAL DOT INDICATOR APPEAR THROUGHOUT THE MISSION. MINUS DENSITY DOTS SPACED 1.7 INCHES APART, LOCATED

3 MAR 1967

Cy No.	Office	Action
1	File	
2	CS	
	SEC BR	
	TDS	
	CCD	
	ICD	
	FD	
	PCD	
	RED-ICB	
342	TID	
	IAD	
	PAG	
	DIAXX-4	
	SPAD	
	NSA-LO	
	DIA-AP	

Advance copy
Sanitized

-2-

1.5 INCHES AND 0.5 INCH FROM THE OUTBOARD EDGE OF THE FORMAT APPEAR FROM THE BEGINNING OF THE MISSION UNTIL FRAME 1200. A PINHOLE OR SMALL GOUGE LOCATED 2.1 INCHES FROM THE OUTBOARD EDGE OF THE FORMAT INTERMITTENTLY APPEARS FROM THE BEGINNING OF THE MISSION UNTIL ABOUT FRAME 1100. PLUS DENSITY FOG STREAKS APPEAR ON FRAMES 01 AND 02. FRAMES 271 AND 279 CONTAIN A PLUS DENSITY FOGGED OVAL 5.5 BY 2 INCHES AT MIDFRAME. FAINT PLUS DENSITY LONGITUDINAL STREAKS APPEAR INTERMITTENTLY THROUGHOUT THE SIDE. FRAME 1083 CONTAINS TWO 1 INCH DIAMETER GROUPS OF PLUS DENSITY SPOTS AT MIDFRAME AND AT THE OUTBOARD EDGE OF THE FORMAT, 6 INCHES FROM THE DATA EDGE. FRAME 1066 CONTAINS A HEAT SPLICE; FRAME 1085 CONTAINS A MANUFACTURING SPLICE. THE OUTBOARD EDGE OF THE FILM WAS CRIMPED ON FRAMES 2331 THROUGH 2335. FRAMES 2334 AND 2335 OVERLAP. LAST FRAME IS 2335.

D. BOTH SIDES: PLUS DENSITY OVALS ASSOCIATED WITH ROLLER CHATTER APPEAR ABOUT 2 INCHES FROM THE INBOARD EDGE, INTERMITTENTLY ON THE 9R SIDE AND REGULARLY ON THE 9L SIDE AFTER FRAME 600. APPROXIMATELY 15 FRAMES CONTAINED SMEARED IMAGERY ASSOCIATED WITH THE VEHICLE MOTION.

3. POSITIVE:

- A. PI SUITABILITY IS GOOD.
- B. PRINTING AND PROCESSING ARE GOOD.
- C. CLOUDS OBSCURED APPROXIMATELY 20 PERCENT OF THE MISSION.

GP-1

S E C R E T

--END OF MESSAGE--